



TM100B25

Drummotor

Product information

www.vandergraafpte.nl

Selection table TM100B25

TYPE	Power (kW)	Beltspeed at 50 Hz (m/s) Beltpull (N)										Min. L (mm) Design B		Full load curr. at 400 V/50 Hz (A)	Weight L=260 (kg)
205 Z	0,37	3,60 95	2,80 120	2,50 135	2,20 155	2,00 175	1,70 205					310		0,85	14
205 PL2		1,50 225	1,40 245	1,35 260	1,10 310	1,00 340	0,80 425	0,70 485	0,60 565	0,50 680					
425 Z	0,18	1,80 95	1,40 120	1,25 135	1,10 155	1,00 170	0,85 200					310		0,6	14
425 PL2		0,75 220	0,70 235	0,65 250	0,55 300	0,50 330	0,40 415	0,36 460	0,30 550	0,24 690					
425 PL3		0,19 835	0,16 990	0,14 1130	0,12 1300							360			
416 Z	0,12	1,25 90	1,10 105	1,00 115	0,85 135							275		0,4	14
416 PL2		0,75 145	0,70 160	0,65 170	0,55 200	0,50 220	0,40 275	0,36 305	0,30 370	0,24 460					
416 PL3		0,14 755	0,12 880	0,10 1055	0,09 1175							310			
616 Z	0,12	0,90 125	0,80 145	0,70 165	0,60 190							310		0,5	14
616 PL2		0,19 580	0,15 735												
616 PL3		0,07 1300										360			
414 Z	0,10	1,10 85	1,00 95	0,85 110								260		0,4	14
414 PL2		0,75 125	0,70 130	0,65 140	0,55 165	0,50 185	0,40 230	0,36 255	0,30 305	0,24 385					
414 PL3		0,19 465	0,16 550	0,14 630	0,12 735	0,10 880	0,09 980	0,06 1300				310			
414 PL4		0,046 1300	0,042 1300	0,040 1300	0,036 1300	0,029 1300	0,027 1300	0,025 1300	0,023 1300	0,019 1300	0,015 1300	360			
414 PL5		0,012 1300	0,008 1300	0,007 1300											
611 Z	0,08	0,80 95	0,70 110	0,60 125								260		0,4	14
611 PL2		0,50 145	0,40 185	0,36 205	0,30 245	0,26 285	0,19 385	0,15 490							
611 PL3		PL3 540	0,10 705	0,07 1005	0,06 1175							310			

Available standard facewidth's: 260 - 275 - 310 - 360 - 410 - 460 - 510 - 560 - 610 - 660 - 710 - 760 - 810 - 860 mm

Minimum facewidth can deviate, see cable exit options.

The total weight of a drummotor grows approx. 1,6 kg per 100 mm

When an electro-mechanical brake is fitted, the minimum facewidth is increased by 75 mm

Available torque Nm: (Beltpull N x Drumdiameter m) / 2

Beltpull/-torque max. : 1300 N / 65 Nm (Imax upon request)

Options

	Specification	Standard	Optional
 CONSTRUCTION	Shafts and bolts	Mild steel	Stainless steel
	Endflanges	Cast iron	Stainless steel
	Shell	Mild steel	Stainless steel
	Junctionbox	Polyamide	Cast iron or stainless steel
	Cable		Shielded or non-shielded
	Sealing mild steel	RB	HD-1
	Sealing stainless steel	CR	FS, HD-1, HD-2
 SHELL	Crowned	•	•
	Cylindrical		•
	Balanced		•
	Lagging, cold vulcanised		•
	Lagging, hot vulcanised		•
	Lagging, FDA approved		•
	Fitted with grooves, patterns		•
 ELECTRO MOTOR	Three-phase asynchronous	•	Other voltages and frequencies on request
	Power supply	230/400 V - 50 Hz	•
	Single phase (230 V 50Hz)		•
	Insulation class	F	•
	Thermal protection		Bi-metal or thermistor
	Run by frequency inverter	•	
 OTHER OPTIONS	Food grade oil		•
	Backstop, mechanical		•
	Brake, electro mechanical		•
	Inclined or vertical position		•
	Other facewidth's		•
	Different shaft designs		•
	Sensorbearing in drum motor		•
 CERTIFICATES	CE	•	•
	UL		•
	CSA		•
	ATEX zone 22, dust		•
	IP69K		•

Our drummotors, an overview

Drummotor type	Drum diameter (mm)	Shaft diameter (mm)	Power (kW)	Speed (m/s)	Beltpull (N)
TM80B20	80	20	0,07 - 0,12	0,11 - 1,15	598
TM100B25	100	25	0,08 - 0,37	0,007 - 3,60	1300
TM113B25	113	25	0,12 - 0,55	0,008 - 4,40	1150
TM127_25	127	25	0,25 - 1,10	0,016 - 2,60	4100
TM138_25	138	25	0,25 - 1,10	0,017 - 2,80	3800
TM160_25	160	25	0,25 - 0,75	0,31 - 3,30	1135
TM160_30	160	30	0,25 - 2,20	0,11 - 4,00	3000
TM215_30	215	30	0,25 - 2,20	0,27 - 5,30	1900
TM215_40	215	40	0,75 - 5,5	0,17 - 4,70	5115
TM215B50	215	50	1,5 - 7,0	0,18 - 0,62	11500
TM273_40	273	40	0,75 - 5,50	0,21 - 5,00	4355
TM315_40	315	40	0,75 - 5,50	0,40 - 5,20	4020
TM315_50	315	50	2,2 - 11,0	0,34 - 4,40	7125
TM315B60	315	60	3,0 - 11,0	0,22 - 1,40	12790
TM400_50	400	50	2,2 - 11,0	0,40 - 4,80	5700
TM400_60	400	60	3,0 - 22,0	0,45 - 4,20	10960
TM500_60	500	60	3,0 - 22,0	0,55 - 4,40	8905
TM500A75	500	75	15,0 - 30,0	1,00 - 3,20	14250
TM500A100	500	100	15,0 - 30,0	0,55 - 1,25	25300
TM620A75	620	75	15,0 - 30,0	1,25 - 3,90	11400
TM630A100	630	100	37,0 - 55,0	1,60 - 4,00	21970
TM800A100	800	100	37,0 - 55,0	2,00 - 5,10	17575
TM800A130	800	130	55,0 - 132,0	2,00 - 4,50	35625

Contact us

Van der Graaf B.V.
De Weijert 14
8325 EM Vollenhove
The Netherlands
Tel.: 0031 527 241 441
sales@vandergraafpte.nl

Representatives

Check our website for your regional
representative
www.vandergraafpte.nl